


Order no.	Packing unit	PS
 <p>Surface-mounted door station with colour camera, door loudspeaker and call button, 2/3-gang</p>		
pure white	1270 66	1
anthracite	1270 67	1
colour aluminium	1270 65	1

Door station with colour camera, door loudspeaker and call button, 2/3-gang, as completely pre-assembled unit for **vertical** surface-mounted installation.

Call buttons not required can be covered with the call-button cover plate **1255 ...**

The surface-mounted door station offers the following product features:

- Fully pre-assembled surface-mounted door station with TX_44 design, allowing quick and clean installation.
- Signal transmission and power supply of devices via reverse-polarity-protected and short-circuit-proof 2-wire bus
- Torsionally rigid surface-mounted housing through aluminium profile.
- Cover frame made of shatter-proof thermoplastic with high resistance to ultraviolet light as well as a scratch-resistant care-free surface.
- Theft protection by means of Torx screws.
- One-man commissioning through simple commissioning procedure.
- Weather-resistant loudspeaker.
- High-quality electret microphone.
- Hands-free feature (voice-controlled talk-back with echo and background noise suppression).
- Audible acknowledgement signal when a call button is pressed.
- Adjustable speech volume.
- White call button illumination with LEDs.
- Sprayed-water proof call-button cover plate made of shock-resistant plastic.
- Name plate of the call button can be exchanged without tools and cover frame removal.
- Professional labelling with the Gira inscription service www.marking.gira.com/en or the Gira inscription software .

The colour camera has the following properties:

- Automatic day/night switching: The camera switches from daytime operation (colour presentation) to night mode (black and white presentation) and back again at a defined ambient brightness. Due to the high degree of light sensitivity in night mode, good presentation results are achieved even with poor lighting conditions.
- LEDs ensure steady illumination of the field of view at close proximity in the night mode.
- Camera can be manually swivelled 20° horizontally and vertically. In conjunction with the wide-angle lens, a very wide field of view results.
- Automatic background lighting compensation.
- Automatic white balance.
- Automatic gain control (AGC).
- Integrated camera heating with temperature detection.
- Sprayed-water proof cover plate.
- Camera cover plate made of shock-resistant plastic. Easy to replace when damaged, e.g. through vandalism.

Order no.	Packing unit	PS
<p>Power supply: 26 V DC \pm 2 V (bus voltage)</p> <p>Connections: two screw terminals for 2-wire bus two screw terminals for additional supply</p> <p>Dimensions: W x H x D 110 x 253 x 19 mm (without camera) W x H x D 110 x 253 x 40 mm (with camera)</p> <p>Name plate dimensions: W x H 62 x 18 mm</p> <p>Image capture element: CCD sensor 1/3"</p> <p>Wide-angle objective: 150° Aperture angle</p> <p>Visible detection range: Angle of detection of the camera 100°</p> <p>Detectable area (with 20° swivelling): 140°</p> <p>Colour system: PAL</p> <p>Pixels: 500 (H) x 582 (V)</p> <p>Horizontal resolution: 380 TV lines</p> <p>Switching threshold colour to B/W operation: 1 lux</p> <p>Light sensitivity in B/W operation: 0.1 lux</p> <p>Electronic shutter close time: up to 1/100000 s</p> <p>IR filter: integrated</p> <p>Recommended camera installation height: 1.50 m</p> <p>Temperature range: -20 °C to +50 °C</p> <p>Protection type: IP 44</p> <p>Video control device 1288 00 → Page 275.</p> <p>Video distributor 1292 00 → Page 276.</p> <p>Keyless In keypad 2605 .., Transponder reader 2606 .., Fingerprint reader 2607 .. → Page 280.</p> <p>Call-button cover plate for call button, 2/3-gang 1255 .. → Page 277.</p> <p>Tri-Wing screw set 1407 00 → Page 277.</p> <p>Inscription sheets 1459 00 → Page 208.</p> <p>Labelling software 1423 00 → Page 209.</p>		

